

PRODUCT DATA SHEET

Aqualine AL 12

The LAUDA Aqualine water baths offer an affordable entry into laboratory thermostating. The equipment range for basic applications in the laboratory stands out for its simple operation with digital LED display and high reliability. The devices have no circulating pumps and no fittings within the bath. Consequently, they are corrosion-resistant, easy to clean or disinfect, and provide maximum use of internal bath space. The heating elements housed under the bath vessel ensure homogenous temperature distribution without localised overheating.



Working temperature min.
25 °C



Working temperature max.
95 °C

Technical Attributes

Aqualine AL 12

Working temperature min.	25 °C
Working temperature max.	95 °C
Ambient temperature min.	5 °C
Ambient temperature max.	40 °C
Temperature stability	0.2 ±K
Application	Inside the bath
Heater power	1.0 kW
Power consumption	1.1 kW
Bath volume min.	2 L
Bath volume max.	12 L
Bath opening width	329 mm
Bath opening depth	300 mm
Bath depth	150 mm
Height top of bath without gable cover	240 mm
Height incl. gable cover	338 mm

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 · 97922 Lauda-Königshofen
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222
info@lauda.de · www.lauda.de
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim · HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser